

नं.सीपीपीआरआई/आरटीआई/2020

1669/1668

दिनांक: 18.02.2020

श्री प्रशांत

सी-202,

राज किशोरी कॉम्प्लेक्स, बहादुरपुर गुमती,

कंकरबाग, पिन - 800020,

बिहार

विषय: सूचना अधिकार अधिनियम- 2005 के अन्तर्गत आपके प्रार्थना दिनांक 23.07.2019 के संबंध में।

महोदय,

कृपया अपने प्रार्थना पत्र दिनांक 23.07.2019 का संदर्भ ग्रहण करें।

इस संबंध में सूचनीय है कि आप द्वारा वांछित सूचना संस्थान के संबंधित विभाग से प्राप्त सूचना पत्र दिनांक 18.02.2020 की एक प्रति इस पत्र के साथ संलग्न की जाती है।

भवदीय,

डा. एम. के. गुप्ता
23.07.2019

(डा. एम. के. गुप्ता)

जन सूचना अधिकारी

संलग्नक: यथोक्त

प्रतिलिपि: निजी सचिव: निर्देशक महोदय, सीपीपीआरआई

श्री एस. एस. गुप्ता,

सीनियर डेवलपमेंट ऑफिसर,

उद्योग सवर्धन और आंतरिक व्यापार विभाग (पेपर सेक्शन),

वाणिज्य एवं उद्योग मंत्रालय, भारत सरकार, नई दिल्ली

o/c

Airday
23/02/2020

**Paper Testing Division
Central Pulp and Research Institute**

CPPRI/PTD/RTI/2019-20/ 3

Dated 18.02.2020

**Subject: Recieved a letter from Shri Prashant , C-202, Raj Kishori Complex , Bahadurpur , Gumti,
Kankar bagh, Bihar under RTI Act 2005 regarding**

Please refer to your letter reference No. CPPRI / RTI / 2020/07 dated 06.02.2020. The information as asked vide your letter is as under –

1.	I would like to know the permissible or acceptable variation paper (Maplitho) GSM	In Clause No. 4.2.1 of IS 1848 (Part I) 2018 - No single test result shall vary by more than ± 5 percent from the nominal substance. Further, the mean of 10/20 test results whichever is applicable) shall not vary from the nominal substance by more than ± 2.5 percent. However, where 2.5 per cent of mean of 10/20 test results (whichever is applicable) as calculated above is less than 1.5 g/m^2 , the tolerance shall be $\pm 1.5 \text{ g/m}^2$.
2.	I would like to know the permissible or acceptable variation paper (creamwove) GSM	
3.	I would like to know the permissible or acceptable variation in paper (Art Paper) GSM	In Clause No. 5.3 of IS 4658 :2019 - The substance of the coated paper and board (art and chromo) shall be as agreed to between the purchaser and the supplier. A tolerance of ± 5 percent for coated paper and coated board shall be allowed on the nominal substance and average tolerance of ± 3 percent for coated paper and ± 4 percent for coated board shall be allowed when tested in accordance with 6 of IS 1060 (Part 1).


18/02/2020

Dr. Ravi Datt Godiyal

Scientist E-II & In-Charge,
Paper Testing Division

✓
Dr. M.K. Gupta
Scientist F & PIO
CPPRI